

#### **ROLLER CONE DRILL BIT**

311.1 MTR417 (AUL-KLS41XP)

 Diameter
 311.1 mm (12 1/4")

 IADC
 417

 Product line
 TechnoPro

TecnoPro bits are designed for drilling water wells, vertical and directional drilling and construction drilling. Sealed bearings, optimum cutting structure and complex body protection provide excellent bit life and performance.

### **Specification**

Bearing type	Roller bearing
Seal	Elastomer seal
Number of nozzles*	4
Thread, API	Pin 6 5/8 Reg
Gross weight, kg	95,7

## **Application**

TechnoPro bit is applied for water drilling in soft abrasive formations with water or mud circulation.

### **Drilling modes recommended**

RPM	180-40
WOB. t	8-25

# **Design features**

Combined circulation (Three side jets and one central jet). Shirttail and leg leading edge hard facing. Leg protection with TC compacts. Chisel inserts.

Near gauge of TCI.

Quality management system is certified to ISO 9001 and API Specification Q1

For the purpose of performance improvement, minor changes of the bit design may be introduced without prior customer notification

VOLGABURMASH, JSC Groznenskaya St. 1 Samara, 443004, Russia Tel./fax: +7 (846) 300-8000

e-mail: mail@vbm.ru

www.vbm.ru

<sup>\*</sup> Standard specification may be changed on customer request