

### **ROLLER CONE DRILL BIT**

508mm GRD111 (V-C11T)

| Diameter     | 508 mm (20") |
|--------------|--------------|
| IADC         | 111          |
| Product line | GrandPro     |

GrandPro bits are designed for multiple drilling of upper well sections (surface hole, conductor hole). Sealed bearings, optimum cutting structure and complex body protection provide excellent bit life and performance.

# **Specification**

| Bearing type       | Open Roller bearing |
|--------------------|---------------------|
| Seal               | None                |
| Number of nozzles* | 1                   |
| Thread, API        | Pin 7 5/8 Reg       |
| Gross weight, kg   | 340                 |

## **Application**

GrandPro bit is applied for drilling of oil and gas wells in Soft formation with water or mud circulation.

#### **Drilling modes recommended**

| RPM    | 600-40 |
|--------|--------|
| WOB. t | 9-31   |

# **Design features**

Central jet
Shirttail and leg leading edge hardfacing
Enhanced thick teeth hardfacing.

Quality management system is certified to ISO 9001 and API Specification Q1

For the purpose of performance improvement, minor changes of the bit design may be introduced without prior customer notification

VOLGABURMASH, JSC Groznenskaya St. 1 Samara, 443004, Russia Tel./fax: +7 (846) 300-8000

e-mail: mail@vbm.ru

www.vbm.ru

<sup>\*</sup> Standard specification may be changed on customer request