



Volgaburmash

ROLLER CONE DRILL BIT

155.6 SLHP617 (AUL-LS61XGD)

Diameter 155.6 mm (6 1/8")

IADC 617

Product line SlimholePro

SlimholePro bits are designed for vertical and directional drilling. Design of SlimholePro bits involves advanced knowledge-intensive technologies and engineering analysis in the state of the art software systems. Significant meterage of the bits is achieved due to premium sealed bearings, using exclusively premium quality materials, complex body protection and optimum cutting structure layout.

Specification

Bearing type Journal bearing
Seal Elastomer seal
Number of nozzles* 3
Thread, API Pin 3 1/2 Reg
gross weight, kg 17

Application

SlimholePro bit is applied for drilling of oil and gas wells in hard abrasive formation with water or mud circulation.

Drilling modes recommended

RPM 300-40
WOB, t 8-12

Design features

Side jet circulation
Shirttail and leg leading edge hardfacing
Leg protection with TC compacts
Chisel inserts

Quality management system is certified to ISO 9001 and API Specification Q1

* Standard specification may be changed on customer request

For the purpose of performance improvement, minor changes of the bit design may be introduced without prior customer notification

VOLGABURMASH, JSC
Grozenskaya St. 1
Samara, 443004, Russia

Tel./fax: +7 (846) 300-8000
e-mail: mail@vbm.ru
www.vbm.ru