



Volgaburmash

ROLLER CONE DRILL BIT

215.9 MTR117 (AUL-KLS11TGP)

Diameter 215.9 mm (8 1/2")

IADC 117

Product line Motor

Motor bits are designed for a wide range of drilling applications. Sealed bearings, optimum cutting structure and complex body protection provide excellent performance.

Specification

Bearing type Journal bearing
Seal Elastomer radial type
Number of nozzles* 4
Thread, API Pin 4 1/2 Reg
Gross weight, kg 32

Application

Motor bit is applied for drilling of oil and gas wells in soft formation with water or mud circulation.

Drilling modes recommended

RPM 280-40
WOB, t 4-23

Design features

Combined circulation (three side jet and on central jet)
Shirttail and leg leading edge hardfacing
Leg protection with TCI
Enhanced thick teeth hardfacing
Single gauge of TC compacts
Near gauge of TCI

Quality management system is certified to ISO 9001 and API Specification Q1

* Standard specification may be changed on customer request

For the purpose of performance improvement, minor changes of the bit design may be introduced without prior customer notification

VOLGABURMASH, JSC
Grozenskaya St. 1
Samara, 443004, Russia

Tel./fax: +7 (846) 300-8000
e-mail: mail@vbm.ru
www.vbm.ru