



# Volgaburmash

## ROLLER CONE DRILL BIT

**215.9 MTR136 (AUL-LS43X)**

Diameter ..... 215.9 mm (8 1/2")

IADC ..... 437

Product line ..... Motor

Motor bits are designed for a wide range of drilling applications. Sealed bearings, optimum cutting structure and complex body protection provide excellent performance.

### Specification

Bearing type ..... Journal bearing  
Seal ..... Elastomer seal  
Number of nozzles\* ..... 3  
Thread, API ..... Pin 4 1/2 Reg  
Gross weight, kg ..... 34.9

### Application

Motor bit is applied for drilling of oil and gas wells in soft formation with water or mud circulation.

### Drilling modes recommended

RPM ..... 180-40  
WOB, t ..... 6-17

### Design features

Side jet circulation  
Shirttail and leg leading edge hardfacing  
Leg protection with TC compacts  
Chisel inserts

**Quality management system is certified to ISO 9001 and API Specification Q1**

\* Standard specification may be changed on customer request  
For the purpose of performance improvement, minor changes of the bit design may be introduced without prior customer notification

VOLGABURMASH, JSC  
Grozenskaya St. 1  
Samara, 443004, Russia

Tel./fax: +7 (846) 300-8000  
e-mail: mail@vbm.ru  
www.vbm.ru