



Volgaburmash

ROLLER CONE DRILL BIT

215.9 MTRP537 (AUM2-LSP53XE)

Diameter 215.9 mm (8 1/2")

IADC537

Product line MotorPro

MotorPro bits with premium sealed journal bearings are designed for drilling with high WOB and RPM using downhole hydraulic motor.

Design of MotorPro bits involves advanced knowledge-intensive technologies and engineering analysis in the state of the art software systems. High bit performance is achieved due to using of high-quality materials, improved reliability bearings, complex body protection and optimum cutting structure layout.

Specification

Bearing type Journal bearing
Seal Elastomer seal
Number of nozzles* 3
Thread, API Pin 4 1/2 Reg
Gross weight, kg 37

Application

MotorPro bit is applied for drilling of oil and gas wells in medium abrasive formation with water or mud circulation.

Drilling modes recommended

RPM280-40
WOB, t4-23

Design features

Sid jet circulation
Shirttail and leg leading edge hardfacing
Leg protection with TCI compacts
Stabilization pad with TC compacts
Energy balanced cutting structure
Chisel inserts

Quality management system is certified to ISO 9001 and API Specification Q1

* Standard specification may be changed on customer request

For the purpose of performance improvement, minor changes of the bit design may be introduced without prior customer notification

VOLGABURMASH, JSC
Grozenskaya St. 1
Samara, 443004, Russia

Tel./fax: +7 (846) 300-8000
e-mail: mail@vbm.ru
www.vbm.ru